

Rittal – The System.

Faster – better – everywhere.

AX compact control cabinet Basic enclosure AX, carbon steel – AX 1213.000

Date : Sep 7, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AX compact control cabinet Basic enclosure AX, carbon steel – AX 1213.000

created: 07.09.2021 build on www.rittal.com/us-en



Product description

Material:	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 1, 12
Type rating according to UL 50E:	Type 1, 12
IK code:	IK10
Supply includes:	Housing with door(s) Flange (gland) plate(s) in enclosure base Mounting plate Punched door strip Lock: 3 mm double-bit
Base material:	Carbon steel

Product description

Dimensions:	Height: 1200 mm (47 ") Width: 1000 mm (39 ")
-------------	---

Depth: 300 mm (12 ")

Material thickness::	Housing: 1.5 mm Door: 2 mm Mounting plate: 2.5 mm
Mounting plate:	Height: 1175 mm (46 ") Width: 945 mm (37 ")
Number of doors:	2
Door catch on right, may be swapped to the left:	yes
3-point locking system:	yes
Lock version:	3-point locking system
No. of locks:	1
Lock Insert:	3 mm double-bit
Flange plate, size:	6
Flange plate, qty:	2
Packaging unit:	1 pc(s).
Weight/packaging unit:	81 kg (178.6 lb.)
EAN:	4028177813205
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	AX Compact enclosure, WHD: 1000x1200x300 mm, sheet steel, with mounting plate, two-door, with 3-point lock system

Approvals

Approvals:	Bureau Veritas DNV-GL Lloyds Register of Shipping UL + C-UL
-------------------	--

Certificates:	Certificate of manufacturer according to RMRS Protection category
----------------------	--

Declarations:	Declaration of conformity
----------------------	---------------------------
