

Rittal – The System.

Faster – better – everywhere.

AX compact control cabinet Basic enclosure AX, carbon steel – AX 1033.000

Date : Sep 8, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AX compact control cabinet Basic enclosure AX, carbon steel – AX 1033.000

created: 08.09.2021 build on www.rittal.com/us-en



Product description

Material:	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 1, 3R, 4, 12
Type rating according to UL 50E:	Type 1, 3R, 4, 12
IK code:	IK10
Supply includes:	Housing with door(s) Flange (gland) plate(s) in enclosure base Mounting plate Punched door strip Lock: 3 mm double-bit
Base material:	Carbon steel

Product description

Dimensions:	Height: 300 mm (12 ") Width: 300 mm (12 ")
-------------	---

Depth: 210 mm (8.3 ")

Material thickness::	Housing: 1.25 mm Door: 1.5 mm Mounting plate: 2 mm
Mounting plate:	Height: 275 mm (11 ") Width: 250 mm (9.8 ")
Number of doors:	1
Door catch on right, may be swapped to the left:	yes
Number of cam locks:	1
Lock version:	Cam
No. of locks:	1
Lock Insert:	3 mm double-bit
Flange plate, size:	1
Flange plate, qty:	1
Packaging unit:	1 pc(s).
Weight/packaging unit:	6.7 kg (14.8 lb.)
EAN:	4028177813458
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	AX Compact enclosure, WHD: 300x300x210 mm, sheet steel, with mounting plate, single-door, with one cam lock

Approvals

Approvals: Bureau Veritas

• •

DNV-GL
Lloyds Register of Shipping
UL + C-UL

Certificates:	Certificate of manufacturer according to RMRS Protection category
----------------------	--

Declarations:	Declaration of conformity
----------------------	---------------------------
