

PRODUCT-DETAILS

ACS355-03E-12A5-4+B063

ACS355-03E-12A5-4+B063 Pn 5,5, I2n 12,5A
IP66.



Información General

Global Commercial Alias	ACS355-03E-12A5-4+B063
Código de producto	3AUA0000058164
ABB Type Designation	ACS355-03E-12A5-4+B063
EAN	6438177224471
Descripción corta	ACS355-03E-12A5-4+B063 Pn 5,5, I2n 12,5A IP66.
Descripción larga	<p>The ACS355 drives are designed to meet the requirements of an extensive range of machinery applications in food and beverage, material handling, lifting, textile, printing, rubber and plastics, and woodworking applications.</p> <p>The drive is user-friendly, yet it provides a wide range of built-in technology such as the safe torque off functionality and sequence programming, reducing the need for additional control electronics. The product offers options and diverse functionality to cater to the needs set for speed and torque control of AC induction and permanent magnet motors.</p>

Clasificación

Country of Origin	China (CN) Finland (FI)
Código arancelario	85044084
Invoice Description	ACS355-03E-12A5-4+B063 Pn 5,5, I2n 12,5A IP66.
Made To Order	No
Cantidad mínima de pedido	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensiones

Peso del product	13.7 kg
Largo del product	277 mm
Alto del producto	477 mm
Product Net Length	277 mm
Ancho del product	246 mm
Embalaje Nivel 1 Largo	970 mm
Embalaje Nivel 1 Alto	305 mm
Embalaje Nivel 1 Ancho	335 mm
Embalaje Nivel 1	1 carton
Unidades	

Technical

Number of Phases	3
Grado de protección	IP66
Enclosure Type NEMA	Type4X
Frequency (f)	50/60 Hz
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Module for cabinet building
Communication Protocol	MODBUS LON DeviceNet PROFIBUS CAN EtherNet/IP PROFINET IO TCP/IP Other Bus Systems
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 1 RS-422 0 RS-485 1 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	5/1
Output Current, Normal Use	12.5 A
Output Power, Light-Overload Use	5.5 kW
Output Power, Normal Use	5.5 kW

Información Adicional

Product Main Type	ACS355 IP66
Product Name	Frequency converter

Clasificaciones

Product Series	ACS355
ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Ambiente

SCIP	47b78137-1890-4ab5-bdc3-447632b81b45 Finland (FI)
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)

Where Used (as part of "kit")

Identifier	Description	Type
3AUA0000157214	ACS355-03E-12A5-4+B063 Solar Pump D; ACS355-03E-12A5-4+B063 Pn 4kW, I2n 12,5A IP66 Solar Pump Drive	Kit

Categorías

Convertidores de frecuencia → Convertidores de frecuencia de baja tensión de CA → Convertidores de frecuencia para maquinaria
 → ACS355 - Machinery Drive

